



Product information

Booster Anti Smoke

Booster Anti Smoke is formulated to stop exhaust smoke due to excessive oil burning.

APPLICATION

Booster Anti Smoke is recommended for all types of fuel, diesel or GLP engines, including these with a turbo compressor. It is highly recommended for vehicles consuming too much oil because of engine wear, exhausting fumes and losing power. **Booster Anti Smoke** is suitable with catalytic converters.

PROPERTIES

Booster Anti Smoke contains a specific polymer which increases the oil viscosity at high temperatures and therefore:

- Stops or decreases excessive smoke emission
- Reduces oil consumption
- Extends engine life
- Improves compression
- Improves oil stability and maintains viscosity

Booster Anti Smoke is based on a combination of chemical polymers, viscosity index improvers, anti-oxidants, corrosion-inhibitors, anti-foamants and detergent/dispersant to create a very solid lubricating film. This film resists high pressures, high temperatures and reduces wear and frictions. The product can be mixed up in mineral, semi-synthetic and synthetic oils.

INSTRUCTIONS FOR USE

At operating temperatures, or while engine is warm, add **Booster Anti Smoke** to the engine oil with engine turned off. After adding, drive the engine for 5-10 minutes. Use at each oil change or as needed between oil changes.

One bottle treats 4 to 6 liters of motor oil.

CAUTION

Before use, read carefully safety instructions on packaging or on safety data sheet.