



Product information

Booster Prezol S

The **Booster Prezol S** range is a product line including superior synthetic compressor oils.

TYPICALS

Viscosity	32	46	68
Density at 15 °C, kg/l	0,830	0,833	0,835
Viscosity 40 °C, mm ² /s	33,22	46,40	68,00
Viscosity 100 °C, mm ² /s	6,20	7,98	10,60
Viscosity Index	138	144	148
Flash Point COC, °C	246	262	268
Pour Point, °C	-60	-39	-48

APPLICATIONS

This compressor oil is recommended for oil-flooded rotary sliding-vane and screw-type compressors, even in the most severe conditions. This compressor oil has low carbon-forming tendencies and minimizes the formation of deposits in the discharge system at the temperature range where these compressors operate. Due to the high quality of this compressor oil, mostly the service interval can be extended.

This high quality fully synthetic compressor oil is based on PAO base oils, with a natural high resistance against oxidation. Under addition of additives this oil meets the following properties:

- low oil consumption due to low volatility
- low carbon-forming tendencies
- very good oxidation stability
- very good protection against corrosion
- very good anti-wear properties
- excellent thermal stability

PERFORMANCE LEVEL

ISO 6743-3A DAJ

By product choice always follow the requirements and instructions of the manufacturer.