



Product information

Booster Ruby 0W-30

The **Booster Ruby 0W-30** is a modern high performance synthetic engine oil developed according the most recent technology recommended for use in petrol and diesel engines of the PSA group.

TIPICALS

SAE	0W-30
Density at 15 °C, kg/l	0,842
Viscosity -35 °C, mPa.s	5920
Viscosity 40 °C, mm ² /s	55,10
Viscosity 100 °C, mm ² /s	9,80
Viscosity Index	165
Flash Point COC, °C	230
Pour Point, °C	-51
Total Base Number, mgKOH/g	6,2
Sulphate Ash, %	0,54

APPLICATIONS

A synthetic, fuel economy, universal motor oil, developed according the most recent technology, based on specially selected synthetic base oils to which advanced additives are added to obtain the following properties:

- a lower fuel consumption
- suitable for modern catalyts
- a very fast cold start
- a safe lubrication film at high temperatures
- extended oil drain intervals
- a very good detergency and dispersion
- a very strong protection against wear, corrosion and foaming

This universal, synthetic, fuel economy, "mid SAPS" motor oil is recommended for use in petrol and diesel engines, with or without turbo-charging, in passenger cars and delivery vans with extended oil drain intervals. Due to its low SAPS content this product can be applied in vehicles with modern three way catalyts and diesel particle filters.

PERFORMANCE LEVEL

ACEA C2
PSA B71 2312

By product choice always follow the requirements and instructions of the manufacturer.